

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : WHITECHEM PU DF 25-B
Product code : DF 25
Type of product : Adhesives, sealants
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AKDE KİMYA END. SAN. ve TİC. LTD. ŞTİ.
Yeşilbayır mahallesi Şimşir sokak No:20
34555 İSTANBUL - TURKEY
T +90 2127710622 - F +90 2127710624
info@akde.net - www.akde.net / www.whitechem.com.tr

1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315 Calculation method
Sensitisation — Respiratory, Category 1 H334 Calculation method

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : 4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate

Hazard statements (CLP) : H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

Precautionary statements (CLP) : P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

smoking
P261 - Avoid breathing dust, fume, gas, mist, vapours
P280 - Wear protective gloves, eye protection, face protection
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P332+P313 - If skin irritation occurs: Get medical advice/attention
P342+P311 - If experiencing respiratory symptoms: Call a doctor, a POISON CENTER
P370+P378 - In case of fire: Use Dry chemical, CO₂, or water spray or alcohol-resistant foam to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

No applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene (Note C)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	10 - 15	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (Note C)(Note 2)	(CAS No) 101-68-8 (EC no) 202-966-0 (EC index no) 615-005-00-9 (REACH-no) 01-211945701447-0000	< 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Specific concentration limits:

Name	Product identifier	Specific concentration limits
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate	(CAS No) 101-68-8 (EC no) 202-966-0 (EC index no) 615-005-00-9 (REACH-no) 01-211945701447-0000	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact : Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

WHITECHEM PU DF 25-B		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Austria	Local name	Xylol (alle Isomeren)
Austria	MAK (mg/m ³)	221 mg/m ³
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m ³)	442 mg/m ³
Austria	MAK Short time value (ppm)	100 ppm

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Austria	Remark (AT)	H
Belgium	Local name	Xylène, isomères mixtes, purs
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Bulgaria	Local name	Ксилен (смес от изомери), чист•
Bulgaria	OEL TWA (mg/m³)	221 mg/m³
Bulgaria	OEL STEL (mg/m³)	442 mg/m³
Croatia	Local name	Ksilen (svi izomeri)
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	221 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti)	442 mg/m³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti)	100 ppm
Croatia	Naznake (HR)	K, EU* K, Xn
Czech Republic	Local name	Xylen technická sm s isomer a (všechny isomery)
Czech Republic	Expoziční limity (PEL) (mg/m³)	200 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	400 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	90 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Xylen, alle isomere (1996)
Denmark	Grænseværdie (langvarig) (mg/m³)	109 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Anmærkninger (DK)	EH
Estonia	Local name	Ksüleen (dimetüülbenseen)
Estonia	OEL TWA (mg/m³)	200 mg/m³
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m³)	450 mg/m³
Estonia	OEL STEL (ppm)	100 ppm
Finland	Local name	Ksyleeni
Finland	HTP-arvo (8h) (mg/m³)	220 mg/m³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m³)	221 mg/m³
France	VME (ppm)	50 ppm
France	VLE (mg/m³)	442 mg/m³
France	VLE (ppm)	100 ppm
Germany	Local name	Xylol(alleIsomeren)
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	440 mg/m³
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm
Germany	Remark (TRGS 900)	DFG,EU,H
Greece	OEL TWA (mg/m³)	435 mg/m³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m³)	650 mg/m³
Greece	OEL STEL (ppm)	150 ppm
Hungary	Local name	XILOL(ok)
Hungary	AK-érték	221 mg/m³
Hungary	CK-érték	442 mg/m³
Hungary	Megjegyzések (HU)	b; EU1
Ireland	Local name	Xylene, mixed isomers
Ireland	OEL (8 hours ref) (mg/m³)	221 mg/m³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m³)	442 mg/m³
Ireland	OEL (15 min ref) (ppm)	100 ppm

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Xilene, isomeri misti, puro
Italy	OEL TWA (mg/m ³)	221 mg/m ³
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m ³)	442 mg/m ³
Italy	OEL STEL (ppm)	100 ppm
Latvia	Local name	Ksilols (o-,m-,p-ksilols, dimetilbenzols)
Latvia	OEL TWA (mg/m ³)	221 mg/m ³
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL STEL (mg/m ³)	442 mg/m ³
Latvia	OEL STEL (ppm)	100 ppm
Lithuania	Local name	Ksilenas
Lithuania	IPRV (mg/m ³)	200 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	450 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Lithuania	NRV (mg/m ³)	0.1 mg/m ³
Lithuania	NRV (ppm)	0.01 ppm
Lithuania	Remark (LT)	O
Luxembourg	Local name	Xylène, isomères mixtes, purs
Luxembourg	OEL TWA (mg/m ³)	221 mg/m ³
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m ³)	442 mg/m ³
Luxembourg	OEL STEL (ppm)	100 ppm
Malta	Local name	Xylene,mixed isomers,pure
Malta	OEL TWA (mg/m ³)	221 mg/m ³
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m ³)	442 mg/m ³
Malta	OEL STEL (ppm)	100 ppm
Netherlands	Local name	Xylen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m ³)	210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	442 mg/m ³
Netherlands	Remark (MAC)	H
Poland	Local name	Ksilen mieszanina izomerów: 1,2-; 1,3-; 1,4-
Poland	NDS (mg/m ³)	100 mg/m ³
Poland	NDSCh (mg/m ³)	0.09 mg/m ³
Portugal	Local name	Xileno (isómeros)
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	150 ppm
Romania	Local name	Xilen (izomeri)
Romania	OEL TWA (mg/m ³)	221 mg/m ³
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m ³)	442 mg/m ³
Romania	OEL STEL (ppm)	100 ppm
Slovenia	Local name	ksilen (mešane izomere)
Slovenia	OEL TWA (mg/m ³)	221 mg/m ³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m ³)	442 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	Local name	Xilenos, mezcla isómeros
Spain	VLA-ED (mg/m ³)	221 mg/m ³
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m ³)	442 mg/m ³
Spain	VLA-EC (ppm)	100 ppm
Sweden	Local name	Xylene
Sweden	nivågränsvärde (NVG) (mg/m ³)	200 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	450 mg/m ³

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	takgränsvärde (TGV) (mg/m ³)	0.05 mg/m ³
Sweden	takgränsvärde (TGV) (ppm)	0.005 ppm
United Kingdom	Local name	Xylene, o-,m-,p- or mixed isomers
United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
Norway	Local name	Xylen (alle isomere)
Norway	Grenseverdier (AN) (mg/m ³)	108 mg/m ³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Switzerland	Local name	Xylène (tous les isomères)
Switzerland	VME (mg/m ³)	435 mg/m ³
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m ³)	870 mg/m ³
Switzerland	VLE (ppm)	200 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Methylene bisphenyl isocyanate (MDI)
Australia	TWA (mg/m ³)	0.02 mg/m ³
Australia	STEL (mg/m ³)	0.07 mg/m ³
USA - ACGIH	Local name	Xylene
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)		
Austria	Local name	Diphenylmethan-4,4'-diisocyanat
Austria	MAK (mg/m ³)	0.05 mg/m ³
Austria	MAK (ppm)	0.005 ppm
Austria	MAK Short time value (mg/m ³)	0.1 mg/m ³
Austria	MAK Short time value (ppm)	0.01 ppm
Austria	Remark (AT)	Sah
Belgium	Local name	4,4'-Diisocyanate de diphénylméthane (MDI)
Belgium	Limit value (mg/m ³)	0.052 mg/m ³
Belgium	Limit value (ppm)	0.005 ppm
Czech Republic	Local name	Difenylmethan-4,4'-diisokyanát
Czech Republic	Expoziční limity (PEL) (mg/m ³)	0.05 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	0.005 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	0.1 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	0.01 ppm
Denmark	Local name	Diphenylmethan-4,4'-diisocyanat
Denmark	Grænseværdie (langvarig) (mg/m ³)	0.05 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	0.005 ppm
Estonia	Local name	4,4'-metüleendifenüül-diisotsüanaat (fenüülisotsüanaat)
Estonia	OEL TWA (mg/m ³)	0.05 mg/m ³
Estonia	OEL TWA (ppm)	0.005 ppm
Estonia	OEL STEL (ppm)	0.1 ppm
France	Local name	4,4'-Diisocyanate de diphénylméthane (3)
France	VME (mg/m ³)	0.1 mg/m ³
France	VME (ppm)	0.01 ppm
France	VLE (mg/m ³)	0.2 mg/m ³
France	VLE (ppm)	0.02 ppm
Germany	Local name	4,4'-Methylenediphenyldiisocyanat
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	0.05 mg/m ³
Germany	Remark (TRGS 900)	DFG,11,12,Sa,Y
Greece	OEL TWA (mg/m ³)	0.2 mg/m ³
Greece	OEL TWA (ppm)	0.02 ppm
Greece	OEL STEL (mg/m ³)	0.2 mg/m ³
Greece	OEL STEL (ppm)	0.02 ppm
Hungary	Local name	difenilmetán-4,4'-diizocianát (MDI)
Hungary	AK-érték	0.05 mg/m ³
Hungary	CK-érték	0.05 mg/m ³

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Hungary	Megjegyzések (HU)	i, sz; l.
Ireland	Local name	4,4'-Methylene-diphenyl diisocyanate (as —NCO)
Ireland	OEL (8 hours ref) (mg/m³)	0.02 mg/m³
Ireland	OEL (15 min ref) (mg/m³)	0.07 mg/m³
Ireland	Notes (IE)	Sen
Lithuania	Local name	Metileno bisfenilizocianatas (MDI)
Lithuania	IPRV (mg/m³)	0.05 mg/m³
Lithuania	IPRV (ppm)	0.005 ppm
Lithuania	NRV (mg/m³)	0.1 mg/m³
Lithuania	NRV (ppm)	0.01 ppm
Poland	Local name	Metilenobis(fenylizocyanian (diizocyanian 4,4'-metylenodifenylu)
Poland	NDS (mg/m³)	0.03 mg/m³
Poland	NDSch (mg/m³)	0.09 mg/m³
Portugal	Local name	Metilenodifenilisocianato (MDI)
Portugal	OEL TWA (ppm)	0.005 ppm
Slovenia	Local name	difenilmetan-4,4'-diizocianat (4,4'-metilendifenil diizocianat)
Slovenia	OEL TWA (mg/m³)	0.05 mg/m³
Slovenia	OEL STEL (mg/m³)	0.05 mg/m³
Spain	Local name	Diisocianato de 4,4'-difenilmetano (MDI)
Spain	VLA-ED (mg/m³)	0.052 mg/m³
Spain	VLA-ED (ppm)	0.005 ppm
Spain	Notes	Sen (Sensibilizante. Véase Apartado 6.)
Sweden	Local name	4,4'-Methylenediphenyl diisocyanate
Sweden	nivågränsvärde (NVG) (mg/m³)	0.03 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	0.002 ppm
Sweden	takgränsvärde (TGV) (mg/m³)	0.05 mg/m³
Sweden	takgränsvärde (TGV) (ppm)	0.005 ppm
Norway	Local name	Difenylmetan-4,4'-diisocyanat (MDI)
Norway	Grenseverdier (AN) (mg/m³)	0.05 mg/m³
Norway	Grenseverdier (AN) (ppm)	0.005 ppm
Australia	Local name	Methylene bisphenyl isocyanate (MDI)
Australia	TWA (mg/m³)	0.02 mg/m³
Australia	STEL (mg/m³)	0.07 mg/m³
USA - ACGIH	Local name	Methylene bisphenyl isocyanate (MDI)
USA - ACGIH	ACGIH TWA (ppm)	0.01 ppm
USA - ACGIH	Remark (ACGIH)	Resp sens

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Black.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.99 - 1.01 g/ml
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1133
UN-No. (IMDG) : 1133
UN-No. (IATA) : 1133
UN-No. (ADN) : 1133
UN-No. (RID) : 1133

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ADHESIVES
Proper Shipping Name (IMDG) : ADHESIVES
Proper Shipping Name (IATA) : ADHESIVES
Proper Shipping Name (ADN) : ADHESIVES
Proper Shipping Name (RID) : ADHESIVES
Transport document description (ADR) : UN 1133 ADHESIVES, 3, III, (D/E)
Transport document description (IMDG) : UN 1133 ADHESIVES, 3, III
Transport document description (IATA) : UN 1133 ADHESIVES, 3, III
Transport document description (ADN) : UN 1133 ADHESIVES, 3, III
Transport document description (RID) : UN 1133 ADHESIVES, 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Danger labels (IMDG)

: 3

:



IATA

Transport hazard class(es) (IATA)

: 3

Hazard labels (IATA)

: 3

:



ADN

Transport hazard class(es) (ADN)

: 3

Danger labels (ADN)

: 3

:



RID

Transport hazard class(es) (RID)

: 3

Danger labels (RID)

: 3

:



14.4. Packing group

Packing group (ADR)

: III

Packing group (IMDG)

: III

Packing group (IATA)

: III

Packing group (ADN)

: III

Packing group (RID)

: III

14.5. Environmental hazards

Dangerous for the environment

: No

Marine pollutant

: No

Other information

: No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)

: F1

Special provisions (ADR)

: 640E

Limited quantities (ADR)

: 5I

Excepted quantities (ADR)

: E1

Packing instructions (ADR)

: P001, IBC03, LP01, R001

Special packing provisions (ADR)

: PP1

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830


Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T2
 Portable tank and bulk container special provisions (ADR) : TP1
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Operation (ADR) : S2
 Hazard identification number (Kemler No.) : 30
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : •3YE

- Transport by sea

Special provisions (IMDG) : 223, 955
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : P001, LP01
 Special packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T2
 Tank special provisions (IMDG) : TP1
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-D
 Stowage category (IMDG) : A
 Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.
 MFAG-No : 127;128

- Air transport

PCA Excepted quantities (IATA) : E1
 PCA Limited quantities (IATA) : Y344
 PCA limited quantity max net quantity (IATA) : 10L
 PCA packing instructions (IATA) : 355
 PCA max net quantity (IATA) : 60L
 CAO packing instructions (IATA) : 366
 CAO max net quantity (IATA) : 220L
 Special provisions (IATA) : A3
 ERG code (IATA) : 3L

- Inland waterway transport

Classification code (ADN) : F1
 Special provisions (ADN) : 640E
 Limited quantities (ADN) : 5 L
 Excepted quantities (ADN) : E1
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01
 Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : F1

WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Special provisions (RID)	: 640E
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference	: Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

Denmark

Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product
-----------------------------------	---

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity, Category 2



WHITECHEM PU DF 25-B

Safety Data Sheet

According to Regulation (EU) 2015/830

Date of issue: 06.09.2017

Revision date:

Supersedes:

Version: 0.0

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Resp. Sens. 1	Sensitisation — Respiratory, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS EU WHITECHEM

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product